





ROMET

Distributed By
MVC
 Meter, Valve & Control
 877-566-3837

Rotary Gas Meters



METER SIZE	ANSI 125 FF FLANGE	A	B	C	D1	D1 (no Mag. Hsg)	D2	D3	D4	E1	WEIGHT (lbs)
RM1000	2"	6.75"	Ø 6.0"	3.08"	10.55"	8.09"	12.03"	12.86"	13.75"	4.0"	12-15

RM1000 - IMPERIAL


IMPERIAL RM1000 2" FLANGE CONNECTION

TECHNICAL SPECIFICATION

Connection (Flanged)	ANSI 125 FF	2"
MAOP	(psig)	175
Flow Capacity	(cfh)	1000
Rangeability @ ± 1% Error		25:1
Rangeability @ ± 2% Error		50:1
Start Rate	(cfh)	1.8
Stop Rate	(cfh)	1.5
Differential @ 100% Flow	(I.W.C.)	0.60
Instrument Drive Rate	(cf/rev)	10
LF Pulser (Optional on Std Ctr)	(cf/pulse)	10

CORRECTED FLOW CAPACITY AND TYPICAL ACCURACY GUIDE

RM1000 METER (SCFH)	
Gauge Pressure P.S.I.G. 0.25	RM1000 Qmax = 1000ft ³ /hr
2	1045
5	1317
10	1656
15	1996
20	2335
25	2675
50	4372
75	6069
100	7766
125	9464
150	11161
175	12858



ROMET

The values quoted are typical of normal production. They do not constitute a specification. Romet Limited reserves the right to change any information in this literature without notice. All of the information and data in this literature has been carefully compiled and thoroughly checked.