

ELSTER-AMCO WATER METERS

WATER METER COUPLINGS

Each meter can be fitted with a set of Union Connectors
A set of Union Connectors includes 2 Nuts – 2 Tailpiece – 2 Gaskets/O-rings
Note: Add Space: 1/16" for Fiber Gasket (Hot Water), 1/8" for Rubber Gasket (Cold Water) The O-rings do not require added space. Couplings are available in waterworks bronze, low lead brass, and polymer upon request.



BRONZE COUPLING DIMENSIONS									
		TAILPIECE		COUPLING					
METER SIZE	COUPLING	TAILPIECE	THREADS	NUT THREADS					
SIZE	SIZE	LENGTH	(ID)	NPMSD (ID)					
1/2"	1/2"	2-1/4"	1/2"	3/4"					
3/4"	3/4"	2-1/2"	3/4"	1"					
1"	1"	2-5/8"	1"	1-1/2"					
1-1/2"	1-1/2"	2-7/8"	1-1/2"	2-1/4"					
2"	2"	3"	2"	2-3/4"					

WATER METER COMPANION FLANGES



BRONZE FLANGES AVAILABLE IN 1-1/2" & 2" SIZES ONLY. CAST IRON FLANGES AVAILABLE IN ALL SIZES. ALL CAST IRON FLANGES ARE 125# RATED AND CONFORM TO ANSI B16.1 CLASS 125.

	FLG	BOLT	FLG	#	BOLT	HOLE	BOLT	WEIGHT			
Size	OD	CIRCLE	THICK	BOLTS	DIA	DIA	LENGTH	#			
OVAL	OVAL										
1-1/2"	5-5/8	4	15/16	2	5/8	5/8	2	4.5			
2"	6	4-1/2	1	2	5/8	5/8	2-1/2	4.5			
ROUND											
1-1/2"	5	3-7/8	9/16	4	1/2	1/2	2-1/2				
2"	6	4-3/4	5/8	4	5/8	5/8	2-1/2				
3"	7-1/2	6	3/4	4	5/8	5/8	2-1/2	19			
4"	9	7-1/2	15/16	8	5/8	5/8	2-1/2	28			
6"	11	9-1/2	1	8	3/4	3/4	3	43			
8"	13-1/2	11-3/4	1-1/8	8	3/4	3/4	3	69			
10"	16	14-1/4	1-3/16	12	3/4	1	3	100			
12"	19	17	1-1/4	12	3/4	1	3	125			

DISTRIBUTED BY



Phone 877-566-3837 Fax 925-407-2903 Direct 925-519-4718 metervalveandcontrol@yahoo.com www.metervalveandcontrol.com

1499 Sunnybrook Rd Alamo, CA 94507