



Master Meter's Multi-Jet meter exceeds the AWWA C708 standard. With sensitivity to measure water flowing as low as 1/8 gallon per minute and accuracy unaffected by common particulates and build-up that would freeze other types, you can count on our Multi-Jet technology.

Technical Specifications:

Register - Standard Direct Read, DIALOG 2G and DIALOG 3G AMR System registers are available. Six wheel odometers are standard. Together, an integrated and migratable technology environment is attained; direct, proximity (touch), mobile AMR, and Fixed Network AMI.

Register Sealing - Direct read and DIALOG® registers are permanently sealed with a scratch resistant glass lens, stainless steel base and wrap-around gasket to prevent intrusion of dirt or moisture.

Design/Operation - Velocity-type flow measurement. Water that is evenly distributed by multiple converging inlet ports flows past an impeller in the measuring chamber, creating an impeller velocity directly proportional to water flow rate.

Features & Benefits:

- Rugged basket strainer built from advanced polymer materials for superior wear mitigation.
- Proprietary design produces smooth, laminar flow profile for improved accuracy
- Award-winning register design houses all vital components – encoder, RF transmitter, battery and antennae – safely within the register's stainless steel and tempered glass enclosure.
- Free of external wires, components and connections – the #1 cause of field related issues on competitive designs.
- Measures with only moving part moving part that is hydro-dynamically balanced on a sapphire bearing to preserve accuracy and promote a positive bottom line.
- Exceptional performance in passing entrained solids and operating in environments with high mineral content.
- Clean, elegant measurement design is highly sensitive to leaks and low flow while limiting wear for excellent revenue protection.



Technical Specs (Cont'd):

- **Register Sealing** - Direct read and DIALOG® registers are permanently sealed with a scratch resistant glass lens, stainless steel base and wrap-around gasket to prevent intrusion of dirt or moisture.
- **Register Unit** - Registration available in U.S. gallons, cubic feet or cubic meters.
- **Test Circle** - Large center sweep hand with one hundred (100) clearly marked gradations on the periphery of the dial face.
- **Low Flow/Leak Indicator** - Center mounted indicator with high sensitivity resulting from direct one to one linkage to measuring element.
- **Register** - Standard Direct Read, DIALOG 2G and DIALOG 3G AMR System registers are available. Six wheel odometers are standard. Together, an integrated and migratable technology environment is attained; direct, proximity (touch), mobile AMR, and Fixed Network AMI.
- **Register Unit** - Registration available in U.S. gallons, cubic feet or cubic meters.
- **Test Circle** - Large center sweep hand with one hundred (100) clearly marked gradations on the periphery of the dial face.

METER OPERATING CHARACTERISTIC/DIMENSION	5/8"	3/4" x 7-1/2"	3/4" x 9"	3/4" x 9" x 1"	1"
Flow Rating (gpm)	20	30	30	30	50
Continuous Flow (gpm)	15	20	20	20	30
Normal Flow Range (gpm)	1-20	2-30	2-30	2-30	3-50
Extended Low Flow (gpm)	1/8	1/4	1/4	1/4	3/8
Maximum Working Pressure (psi)	150	150	150	150	150
Maximum Working Temperature (F)	120	120	120	120	120
Length (A below)	7-1/2"	7-1/2"	9"	9"	10-3/4"
Width (B below)	3-5/8"	3-5/8"	3-5/8"	3-5/8"	4"
Height, standard register with lid (C below)	5"	5"	5"	5"	5-1/4"
Height, bottom to center line (D below)	1-1/2"	1-1/2"	1-1/2"	1-1/2"	1-3/4"
Weight (lbs)	3.95	4.0	4.1	4.6	5.25
Packed To Carton	6	6	6	4	4
Carton Weight (lbs)	25.1	25.4	26	19.8	22.4

Accuracy and Head Loss Chart

